



TECHNICAL SPECIFICATION

Standard



Optional



| | | |
|-----------|----------------|--|
| LEAF TYPE | Leaf Thickness | 53mm |
| | Surface Finish | Coated (Lacquered) |
| | Edge | Standard: 0.8mm PVC + Coated Optional: Direct Painting Application |
| | Facing | 4mm MDF |
| | Core Type | Solid Fire Core 44mm |
| | Rails & Stiles | N/A |
| | Lipping | 10mm Hardwood Lipping |
| | Groove | Optional |
| | Molding | Optional |
| | Rebate on Leaf | Optional |

| | | |
|------------|--------------------|---|
| FRAME TYPE | Frame Material | Standard: MDF Optional: Hardwood |
| | Material Thickness | Standard: 42mm MDF Optional: 40mm Hardwood |
| | Architrave | Standard: 8x80mm MDF Optional: 12x80mm / 18x80mm / 18x100mm |
| | Surface Finish | Coated (Lacquered) |
| | Rebate On Frame | Optional |

| | | |
|------------|-------------------------|---|
| DIMENSIONS | Standard Wall Width | Single: 800 / 900 / 1000mm Double: 1400 / 1600 / 1800mm |
| | Standard Wall Height | 2100 / 2200mm |
| | Standard Wall Thickness | 110 150 170 210mm |
| | Max Wall Width | Single: 1300mm Double: 2300mm |
| | Max Wall Height | Single: 3100mm Double: 2800mm |
| | Max Wall Thickness | 240mm |
| | Doorset Option | Single & Double |

| | | |
|----------------|---------------|--|
| OTHER FEATURES | Hardwares | Optional |
| | For Glazing | Optional |
| | For Louver | N/A |
| | Gasketing | 10x4mm Intumescent Seal |
| | Acoustical | Optional |
| | Fire Rating | 30 min. |
| | Certification | EN 1634-1 - BS 476-22 - ISO 9001 - ISO 14001 |
| | Transom Panel | Overpanel max. 1500mm |