



TECHNICAL SPECIFICATION

Standard



Optional

LEAF TYPE	Leaf Thickness	50mm
	Leaf Surface Material	Galvanize
	Surface Finish	Powder Coated
	Leaf Sheet Thickness	Standard: 1,0mm, Optional: 1,2mm
	Core Type	50 kg/m ³ - 50mm Rockwool
	Reinforcement	Standard: Hinge Reinforcement, Optional: Stiffener
	Rebate on Leaf	N/A

FRAME TYPE	Frame Type	Standard: Block Frame, Optional: Full Frame
	Frame Material	Galvanize
	Material Thickness	Standard: 1,6mm, Optional: 2,0mm
	Architrave	50mm
	Surface Finish	Powder Coated
	Rebate On Frame	N/A

DIMENSIONS	Standard Wall Width	1000mm
	Standard Wall Height	2100mm
	Standard Wall Thickness	150 - 180mm
	Min - Max Wall Width	800 - 1200mm
	Min - Max Wall Height	1800 - 2410mm
	Min - Max Wall Thickness	100 - 390mm

OTHER FEATURES	Hardwares	Optional
	Glazing	Optional
	Louver	N/A
	Gasketing	Frame Gasket & Intumescent Gasket
	Acoustical	N/A
	Fire Rating	UL10b 90min.
	Smoke Proof	N/A
	Certification	EEA – 2200 – 0038
	Transom Panel	N/A