



Standard



Optional

TECHNICAL SPECIFICATION

| | | |
|-----------|-----------------------|--|
| LEAF TYPE | Leaf Thickness | 50mm |
| | Leaf Surface Material | Galvanize |
| | Surface Finish | Powder Coated |
| | Leaf Sheet Thickness | Standard: 1,0mm, Optional: 1,2mm |
| | Core Type | 50 kg/m ³ - 50mm Rockwool |
| | Reinforcement | Standard: Hinge Reinforcement, Stiffener |
| | Rebate on Leaf | N/A |

| | | |
|------------|--------------------|---|
| FRAME TYPE | Frame Type | Standard: Block Frame, Optional: Full Frame |
| | Frame Material | Galvanize |
| | Material Thickness | Standard: 1,6mm, Optional: 2,0mm |
| | Architrave | 50mm |
| | Surface Finish | Powder Coated |
| | Rebate On Frame | N/A |

| | | |
|------------|--------------------------|---------------|
| DIMENSIONS | Standard Wall Width | 1800mm |
| | Standard Wall Height | 2100mm |
| | Standard Wall Thickness | 150 - 180mm |
| | Min - Max Wall Width | 1400 - 2200mm |
| | Min - Max Wall Height | 1800 - 2410mm |
| | Min - Max Wall Thickness | 100 - 390mm |

| | | |
|----------------|---------------|-----------------------------------|
| OTHER FEATURES | Hardwares | Optional |
| | Glazing | Optional |
| | Louver | N/A |
| | Gasketing | Frame Gasket & Intumescent Gasket |
| | Acoustical | N/A |
| | Fire Rating | UL10b 90min. |
| | Smoke Proof | N/A |
| | Certification | EEA – 2200 – 0039 |
| | Transom Panel | N/A |